

CSI Middle East L.L.C

Your Machinery Partner



SALES/SPARES/SUPPORT



sales@csime.ae info@csime.ae



+971 50 17 71674 +971 56 25 44504

GM900

Super High speed overlock sewing machine with direct drive

GM900-3Z/-4Z/-5Z GM900-3DZ/-4DZ/-5DZ















This series overlock is built-in mini servo motor for direct drive, fine and stable control system.

The machine is designed with fashionable appearance and world advanced mechanism.

Many models have features of automatic thread trimmer, automatic presser foot linter, pneumatic rubbish colejection device (optional).

The score is high efficiency of energy saving This series of overlock sewing machines is equipped with ball bearing or needle bearing which makes it running light and smooth, fully closed lubrication system, slime oil non-die cooling device, fine adjustment of differential feed dog and knob-type stitch regulator.

It is also convenient to the thread, the knife and the loopers and can perform overlock and coverage on all kinds of fabric from light to medium heavy weight as an efficient sewing equipment in knitting and garment factories. GM900-3Z Three threads super high speed overlock with direct drive.

GM900-3DZ Three threads super high speed overlock with automatic thread trimmer and direct drive.

GM900-4Z Four threads super high speed overlock with direct.

GM900-4DZ Four threads super high speed overlock with automatic thread trimmer and direct drive.

GM900-5Z Five threads super high speed overlock with direct drive.

GM900-5DZ Five threads super high speed overlock with automatic thread trimmer and direct drive







Main techical specifications

型号 Model	最高键速 Max.sewing speed	机针 Needle size	机针数 Number of needle	題线数 Number of thread	线速长度 Stitch length	級速度度 Stitch width	压焊提升 Presser foot lift	差功比 Differential natio	自动剪线 Auto trimmer	自动抬压牌 Auto presser foot lifter
GM900 - 3Z	7000 r.p.m.	DC × 27 11"	1	3	3.6 mm	4 mm	5.5 mm	0.7 - 2	0	0
GM900 - 3DZ	7000 r.p.m.	DC × 27 11*	1	3	3.8 mm	4 mm	5.5 mm	0.7 - 2	*	*
GM900 - 4Z	7000 r.p.m.	DC × 27 11*	2	4	3.8 mm	4 mm	5.5 mm	0.7 - 2	0	0
GM900 - 4DZ	7000 r.p.m.	DC × 27 11°	2	4	3.8 mm	4 mm	5.5 mm	0.7 - 2	*	*
GM900 - 5Z	7000 r.p.m.	DC × 27 14*	2	5	5 mm	4 mm	5.5 mm	0.7 - 2	0	0
GM900 - 5DZ	7000 r.p.m.	DC × 27 14*	2	5	5 mm	4 mm	5.5 mm	0.7 - 2	*	*