

GC24608 Series

Two needle post bed lock Stitch



iHighlead



Sewing speed: 1600~2000R.P.M

Post bed, compound feed, single/double needles

Suitable for :-

Car seats, suitcase, bag, shoes, handbag,etc



HIGHLEAD.

GC24608 Post-bed compound feed lockstitch sewing machine

This machine is post bed lockstitch sewing machines with compound feed mechanism. It has three sub models of single needle left-side stitching machine, single needle right side stitching machine and two needle post bed compound feed machine, to meet different demands from the market, with the features of free stitching, beautiful stitches, easy bobbin changing, it is available for stitching car seat, bag and case, boots, hand bags, etc...

GC24608-1L/1R Single needle post-bed compound feed lock stitch (Lift-side stitching bed/Right-side stitching bed)

GC24608-1LD/1RD Single needle post- bed compound feed lock stitch with thread trimmer(Lift-side stitching bed/ Right-side stitching bed)

GC24608-2 Twin-needle post- bed compound feed lock stitch

GC24608-2D Twin needle post-bed compound feed lock stitch with thread trimmer

GC24608-2Q Twin needle post-bed compound feed lock stitch (Pneumatic foot lifter, Pneumatic reverse feeding)

GC24608-1LQ/1RQ Single needle post bed compound feed lock stitch with trimmer Lift-side stitching bed /Right-side stitching bed) (Pneumatic foot lifter, Pneumatic reverse feeding)

GC24608-25R Long arm single needle post bed compound feed lock stitch with trimmer(Right-side stitching bed) (Pneumatic foot lifter, Pneumatic reverse feeding)



The special design of the post bed is convenient for maintenance as well as for sewing curved articles and corners.



Model	GC24608-1L/1R	GC24608-2	GC24608-1LD/1RD	GC24608-2D	GC24608-1LQ/1RQ	GC24608-2Q	GC24608-25R
Max.sewing speed				2000 r.p.m			1600 r.p.m
Needle Bar Stroke				36 mm			
Stitch length				0 - 7 mm			
Presser foot lift	By Knee 16mm By Hand 8mm			Pneumatic presser foot lifting 16mm			
Presser foot alteration				2 - 6 mm			
Reverse feeding device	By Hand			Pneumatic			
Presser foot lifting	By Hand			Pneumatic			
Auto thread trimmer	○	★			○		
Needle size				DP x 17 22# - 24#			
Heightness of post-bed				178 mm			
Lubrication				Semi auto lubrication			Manual
Motor	370 Watts Clutch motor 1400 r.p.m			220V 550W Servo motor			
Needle gauge	GC24608-2	GC24608-2D	GC24608-2Q	8mm (Standard) 9.5mm (Special)			

CSI

CSI MIDDLE EAST LLC SHARJAH

س.ا.م.ا. ميل بست ذمم الشارقة YOUR MACHINERY PARTNER

sales@csime.ae
info@csime.ae

+971 50 1771674
+971 56 25 44504